

Features

- Great cost-effective for front-lit display
- White opaque substrate for front-lit display
- Matte & Glossy surface available
- Best suited for Indoor or outdoor front-lit display under moderate weather conditions

Applications



Technical Data Sheet

Item Code	FL206	Test Method
Base Fabric	300D*500D 18*12	DIN EN ISO2060
Weight (GSM)	380	DIN EN ISO2286-2
Tensile Strength	Warp (N/5cm)	680
	Weft (N/5cm)	620
Tear Strength	Warp (N/5cm)	90
	Weft (N/5cm)	70
Adhesion Strength	N/A	DIN53357:1982
Temperature	-30°C/+70°C	ISO13934-1:1999
RF Weldable (Heat Sealable)	YES	DIN53354
Flame Retardant	B1/M1/M2/NFPA701	

Information contained in this document is based on our general experience and is given in good faith. But we are unable to accept responsibility in respect to factors which are outside our knowledge or control.

Ink Printability

SOLVENT	ECO-SOLVENT	UV	LATEX	SCREEN PRINTING
■	■	■	■	■



Add: Room 912, No.3 Building, Shangdong Business Center, Haizhou District,
Haining, Zhejiang, China
Tel: +86-573-80776996 Fax: +86-573-80776998
Mob/Skype/Wechat: +86-15858322153
mailto:hncomax@163.com jeffcheung@hncomax.com

